



The Limescale Filter and Portable RV Limescale Conditioner is designed to be installed into $\frac{3}{4}$ " water line. Use Teflon tape and pipe thread compound on all threads.

Locate the extra parts that came with your filter. You will find a housing handle and a 7oz bag of polyphosphate packed inside the filter. Install the filter with the water flowing with the direction arrows on the filter top.

Approximately every 6-8 months, check the level of poly-phosphate, and clean the Hard Water Bullet core and the 50 mic filter at this time if needed. The filter holds 7 oz. poly-phosphate and can be purchased from our site. Remove the bottom half of the filter housing to access the filter, bullet core and poly-phosphate crystals.

Remove the screen filter, clean and pour up to 7 oz of polyphosphate into the



filter as shown. You can also remove the gray bullet tube and slide the core out, and clean it at the same time. Keeping your conditioner clean and full will ensure it works at its

best performance.



Remove the Water Conditioner core from the inner tube and soak in vinegar for about an hour as needed. Using a stiff wire brass brush while rinsing under running water works well for removing any deposits.



Reinstall the metal core, **making sure that the bevel is pointing UP** and then re-install the entire bottom assembly to the top housing.

Silkwater Technologies Ltd, Hadera Israel

P: +972-50-4040309

www.silksoftwater.com